




## Adapter cables 19-pin plug (m)

Illustration	Model	Length	Ref. No.
	19-pin plug to DVI-D plug (m)	35 cm	7487 000 101
	19-pin plug to DVI-D socket (f)	35 cm	7487 000 102
	19-pin plug to HDMI plug (m)	35 cm	7487 000 103
	19-pin plug to HDMI socket (f)	35 cm	7487 000 104

## Adapter plates with cable and plug for installation cables 19-pin

Please pay attention to the quality of the supply cable. We recommend to use cables of not more than 2 m length!

Illustration	Model	Specification	Length	Ref. No.
	DVI socket (f)	Half plate 54 x 54 mm, Required installation depth: 67 mm	35 cm	7441 000 560
		Half plate 50 x 50 mm Required installation depth: 67 mm	35 cm	7444 000 560
	HDMI socket (f)	Half plate 54 x 54 mm Required installation depth: 67 mm	35 cm	7441 000 561
		Half plate 50 x 50 mm Required installation depth: 67 mm	35 cm	7444 000 561

## KINDERMANN MEDIAROLLER 30


Ideal for:

- The temporary use during events
- In combination with mobile units
- In case of emergency, e.g. failure of permanent installations



The MediaRoller makes the active transmission of analogue pictures, audio and digital control signals possible up to a distance of 30 m.

Supplied with adapter cables for transmitting VGA, video, S-video, stereo audio or control signals.

Illustration	Model	Specification	Length	Ref. No.
	MediaRoller 30	<p>Cable drum with integrated VGA amplifier, switcher for mode and the following connections:</p> <ul style="list-style-type: none"> <li>• VGA without DDC (via built-in amplifier)</li> <li>• Composite video</li> <li>• Selectable: <ul style="list-style-type: none"> <li>S-video or RS232 (9-pin) linear, bi-directional, crossed bi-directional or audio stereo via 3.5 mm jack</li> </ul> </li> </ul>	30 m multicore cable	7497 000 030